



SPECIFICATION SHEET

MIN. WALL THICKNESS: 87.5%

2-3/8" P-110 5.95 LBS/FT, 8RD

PIPE BODY DATA

NOMINAL OD (in.)	2.375
NOMINAL ID (in.)	1.867
NOMINAL WEIGHT (lbs/ft)	5.95
AVERAGE JOINT WEIGHT (lbs)	190
AVERAGE LENGTH	32'
PIPE GRADE	P-110
NOMINAL WALL (in.)	0.152
TUBE DRIFT (in.)	1.901
BODY YIELD STRENGTH (lbs)	165,000
COLLAPSE (psi)	18,700
INTERNAL YIELD (psi)	20,600
SPECIFIED MINIMUM YIELD STRENGTH (psi)	110,000
CAPACITY (BBL./LIN. FT.)	0.00339
CAPACITY (LIN. FT./BBL.)	295

CONNECTION DATA

CONNECTION	8RD
CONNECTION OD (in.)	3.063
CRITICAL SECTION AREA (sq. in.)	1.503
CONNECTION ID (in.)	1.867
COMPRESSION STRENGTH (lbs)	250,000
EXTERNAL PRESSURE CAPACITY (psi)	17,400
INTERNAL PRESSURE CAPACITY (psi)	19,100
JOINT YIELD STRENGTH (lbs)	250,000
BENDING (100 ft)	220 deg
MAKE-UP TORQUE MINIMUM (ft-lbs)	2210
MAKE-UP TORQUE OPTIMUM (ft-lbs)	2950
MAKE-UP TORQUE MAXIMUM (ft-lbs)	3680

Note: All used figures have **NO** safety factor included for tension, temperature, or general S.F. etc.

The technical information contained herein, including the product performance sheet and other attached documents, has been extracted from information available from the manufacturer and is for reference only and not a recommendation. The user is fully responsible for the accuracy and suitability of use of the technical information. Concentric Pipe and Tool Rentals cannot assume responsibility for the results obtained through the use of this material. No expressed or implied warranty is intended. No safety factor is applied. The information provided for various inspection classes and for various wear conditions (remaining body wall) is for information only and does not represent or imply acceptable operation limits. It is the responsibility of the customer and the end user to determine the appropriate performance ratings, acceptable use of the product, maintain safe operational practices, and to apply a prudent safety factor suitable for the application.